


Blue colored sizes denotes popular DC items

BOND-SEAL SEALING WASHER



- The BOND-SEALER™ sealing washer is EPDM vulcanized to a 20 Gauge galvanized backing.
- TRI-SEAL® long life coated for superior corrosion protection.



U.S. Pat. No. 8,360,701
Taiwan Pat No. 150140
Europe Pat No. 2286067



HEAD TYPE
#12 dia: 5/16" HWH
1/4" Dia: 3/8" HWH
*1/4 dia: 5/16" & 3/8"HWH
5/16 dia: 3/8" HWH



WASHER DETAILS
20 ga G-90 Galvanized Steel
Vulcanized to .062" thick non-conductive EPDM
15MM OD Washer



Special sizes available upon request.



FLANGE-SEAL HEAD with EPDM WASHER



- FLANGE-SEAL™ self-sealing fastener has a deep undercut head that entraps the EPDM sealing washer to assure a leak free seal.
- TRI-SEAL® long-life coated for superior corrosion protection.



WASHER DETAILS
.125" Thick EPDM
Non-conductive

HEAD TYPE
5/16" HWH with Flange Undercut



SCREW AND POINT	DRILL AND TAP CAPACITIES						
	.036"	.100"	.175"	.210"	.250"	.375"	.500"
#8-18 BLAZER-2							
#10-16 BLAZER-3							
#12-14 BLAZER-3							
#12-24 BLAZER-4							
#12-24 BLAZER-5							
1/4-14 BLAZER-1 VRT							
5/16-12 BLAZER-3							
1/4-14 BLAZER-3							
1/4-20 BLAZER-5							

MATERIAL: C1018-1022 Carbon Steel
PLATING: TRI-SEAL® Coating (1,000hrs Salt Spray - ASTM B117).
Exceeds ASTM B633 and F1941 Standards
Dimensions: Meets or exceeds SAE J78 Standards

SIZES AND PERFORMANCE SPECIFICATIONS

DIAMETER AND POINT		LENGTH	Load Bearing Length (Max)	Box Qty	LIST PRICE
A	#12-14 BLAZER-2	x	3/4"	.125"	5M
			1"	.250"	3.5M
			1-1/4"	.625"	3M
			1-1/2"	.750"	2M
			2"	1.25"	2M
			2-1/2"	1.75"	1M
B	1/4-14 BLAZER-1 VRT	x	*7/8" VRT	.325"	2.5M
C	1/4-14 BLAZER-3	x	3/4"	.125"	2.5M
			*1"	.250"	2.5M
			*1-1/4"	.625"	2M
			1-1/2"	.875"	2M
			2"	1"	1.5M
			2-1/2"	1.50"	1M
			3"	.50" - 2"	1M
			4"	.50" - 3"	500
			5"	1" - 4"	500
			6"	2" - 5"	250
D	5/16-12 BLAZER-3	x	1"	.250"	1.5M
			1-1/2"	.875"	1M
			2"	1.25"	1M
			3"	2.25"	750
			4"	3.25"	500
			6"	2.50 - 5"	500
			8"	4.25" - 7"	200
			E	#12-24 BLAZER-5	x
1-1/2"	.625"	2M			
2"	.750"	3M			
F	1/4-20 BLAZER-5	x	1-1/2"	.500"	2M
			2-1/4"	1.250"	1M
			3-1/8"	2-1/8"	1M
			4"	3"	250
			5"	4"	250
			6"	2.50" - 5"	250
			8"	4.25" - 7"	150

FLANGE-SEAL HEAD


G	#12-14 BLAZER-3	x	1"	.250"	3.5M
			1-1/4"	.625"	3M
			1-1/2"	.750"	2M
			2"	1.250"	2M
			2-1/2"	1.5"	1.5M
			3"	2.25"	1M
H	1/4-14 BLAZER-1 VRT	x	7/8" VRT	.325"	2.5M
			1"	.250"	2.5M
I	1/4-14 BLAZER-3	x	1-1/4"	.625"	2.5M
			1-1/2"	.875"	2M
			2"	1"	1.5M

Proper Fastener Installation




CORRECT

Slight circle of sealant extrudes to outer edge.



TOO TIGHT!

Metal backing begins to turn up.



TOO LOOSE

Sealant is not compressed and can not form a seal.

To assure a proper seal, torque the fastener until the EPDM sealant extrudes to the outer edge of the backing material.

All information is non-binding and without guarantee. Before using the products, all specifications and calculations must be checked by a suitably qualified person and local regulations must be observed. This document is subject to revision. We reserve the right to make technical changes. (0321-1)