

Wood or Metal



TRACER® TYPE S Fine Thread

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/ Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)	PRICE
6 x 1"	3/8" - 5/8"	10	
6 x 1-1/8"	3/8" - 3/4"	10	
6 x 1-1/4"	3/8" - 7/8"	8	
6 x 1-5/8"	3/8" - 1-1/4"	5	
6 x 2"	1" - 1-5/8"	3.5	
6 x 2-1/4"	5/8" - 1-7/8"	3	
7 x 2-1/2"	7/8" - 2-1/8"	2.5	
8 x 3"	1-3/8" - 2-1/8"	2	
10 x 3-1/2"	1-7/8" - 3-1/8"	1	
10 x 4"	2-3/8" - 3-5/8"	1	

Phos and oil

SPECIFICATIONS

Head: Bugle Head with #2 Cross Recess
Finish: Phosphate (24hrs. salt spray)
TRACER® fasteners conforms to ANSI/ASME B18.6.4 and ASTM C1002-01
ASTM C1513-04



TRACER HL | HIGH LOW

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/ Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)	PRICE
6 x 1"	3/8" - 5/8"	10	
6 x 1-1/8"	3/8" - 3/4"	8	
6 x 1-1/4"	3/8" - 7/8"	8	
6 x 1-5/8"	1/2" - 1-1/4"	5	
6 x 1-7/8"	3/4" - 1-1/2"	4	
7 x 2-1/4"	1-1/16" - 1-7/8"	2.5	
8 x 2-1/2"	15/16" - 2-1/8"	2.5	
8 x 2-5/8"	1-3/8" - 2-1/4"	2.5	
8 x 3"	1-7/8" - 2-5/8"	2	



TRACER® TYPE "G" Laminating Screw

Attachment or lamination of layered drywall.

Size/ Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)	PRICE
10 x 1-1/2"	3/4" - 1"	5	

Phos and oil

SPECIFICATIONS

Head: Bugle Head with #2 Cross Recess
Finish: Phosphate (24hrs. salt spray)
TRACER® fasteners conforms to ANSI/ASME B18.6.1 and ASTM C1002-01



TRACER® TYPE W Coarse Thread

Attachment of drywall to wood stud or framing.

Size/ Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)	PRICE
6 x 1"	3/8" - 5/8"	10	
6 x 1-1/8"	3/8" - 3/4"	10	
6 x 1-1/4"	3/8" - 7/8"	8	
6 x 1-5/8"	3/8" - 1-1/4"	5	
6 x 2"	1" - 1-5/8"	3.5	
6 x 2-1/4"	5/8" - 1-7/8"	3	
7 x 2-1/2"	7/8" - 2-1/8"	2.5	
8 x 3"	1-3/8" - 2-5/8"	2	
10 x 3-3/4"	2-1/8" - 3-3/8"	2	
10 x 4"	2-3/8" - 3-5/8"	1	

Phos and oil

SPECIFICATIONS

Head: Bugle Head with #2 Cross Recess
Finish: Phosphate (24hrs. salt spray)
TRACER® fasteners conforms to ANSI/ASME B18.6.1 and ASTM C1002-01



Need additional corrosion protection?

Now available with our TRI-SEAL® coating for treated lumber applications!

Size: #6 x 1-1/4" GP Coarse thread. Phillips bugle head.
1,000 hrs salt spray



TRACER® Trim Head

Attachment of drywall to steel stud up to 20 gauge (.036").

Size/ Length	Drywall Thickness Minimum-Maximum	Carton Quantity (M)	PRICE
6 x 1-5/8"	1/2" - 1-1/4"	5	
6 x 2-1/4"	5/8" - 1-7/8"	3	
6 x 3"	3/4" - 2-5/8"	2	

Phos and oil

SPECIFICATIONS

Head: Bugle Head with #1 Square Recess
Finish: Phosphate (24hrs. salt spray)
TRACER® fasteners conforms to ANSI/ASME B18.6.4 and ASTM C1002-01



TRACER® Pan Head

Attachment of steel stud to steel track or for splicing steel stud up to 20 gauge (.036") total thickness.

Size/ Length	Carton Quantity (M)	PRICE
7 x 7/16"	10	

Phos and oil

DISCLAIMER: All information is non-binding and without guarantee. Before using the products, all specifications and calculations must be checked by a suitably qualified person and local regulations must be observed. This document is subject to revision. We reserve the right to make technical changes. (0321-1)